



/ SOMETHING BEGINNING WITH

/ CARE & MAINTENANCE

POWDER COATED METAL

Use a soft clean cloth once weekly to remove particles which can abrade the surface with wear. Avoid contact with liquid, heat and direct sunlight. Abrasive cleaning products are not recommended

LAMINATE TOPS

Use laminate cleaner and soft clean cloth to remove dust and marks. Abrasive cleaning products are not recommended.

FABRIC UPHOLSTERY

Vacuum fabrics on a weekly basis to remove dust, and dirt. Tend to spills and stains as soon as possible. Please contact a specialist fabric cleaner for professional cleaning.

LEATHER UPHOLSTERY

Wipe over leather with a clean damp cloth on a weekly basis to remove particles and dust that can work into the hide and abrade. Creases, stretch marks, scars and insect bites that the animal acquires during its life are natural characteristics of quality leather. As leather is a natural product, softening and stretching is to be expected with use. Please contact a specialist leather cleaner for professional cleaning.

GLASS

Use window cleaner and soft clean cloth to remove dust and marks.

MARBLE

Clean with warm soapy water, or a wet cloth. For stubborn stains use a creme cleaner with a soft sponge or cloth. Do not leave any liquid for extended periods as this will penetrate the stone and may stain.

LACQUERED TIMBER

As timber is sealed with a protective coating, the only maintenance required is to regularly wipe timber with a damp cloth to remove dust and dirt. Oils or other polishes are not recommended. Do not wet down or leave spills to sit on timber surfaces. Avoid contact with liquid, heat and keep out of direct/reflective sunlight. Take care when placing unglazed ceramics as they may scratch the surface. Abrasive cleaning products are not recommended.

OUTDOOR

For longevity please keep furniture in covered outdoor areas away from direct sunlight or harsh weather conditions for extended periods. Timber, steel and leather finishes will naturally discolour with age in an outdoor setting. For timber products re-apply a UV-stable exterior grade oil (eg decking oil) every 6 months.